

Subhead-10
Digital Conference & Multimedia Systems

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.1 DIGITAL CONFERENCE SYSTEM (Wired)

10.1.1 CENTRAL UNIT

Supply, Installation, testing and commissioning of the central unit with digital display (integrated controller & power supply).

The central unit shall have the following technical features or equivalent :

Web browser-system set-up: CU configuration, delegate set up, seat assignment to the seat, input / output control.

Quantity Component

- 1 CCSD-CU Control Unit
- 1 Mains power cord
- 1 24 VDC power supply
- 2 Sets of chairperson's buttons for a Discussion Device
- 1 Exchange tool for buttons
- 1 Set of feet for table top use
- 1 Set of 19" 1U mounting brackets
- 1 Safety instructions
- 1 Installation note
- 1 DVD with operation manual and supporting tools

Specification

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

- Front of unit: 1 x 3.5 mm (0.14 in) stereo headphone socket 1 x USB connector
- Rear of unit: 1 x micro USB connector, 4 x RCA outputs for individual microphone recording
- Built in recorder
- 1 x 4-pole circular female 24 VDC power input Connector
- 2 x 6-pole circular female connectors for loop-through connection of 40 Discussion Devices per trunk

Mechanical

Mounting : Tabletop

Temperature range: 5° to 45° C

Certifications :

The system in general conforms to the IEC 60914 standard.

Approvals: CE, WEEE1, UL, FCC, CSA, ICES-003, EPS1, CCC1, BSM11, EAC

Warranty: Minimum 1 Year

Accepted/approved by the engineer-in-charge.

Each

192,401.00

192,390.00

192,348.00

192,348.00

10.1.2 TABLE TOP CHAIRMAN UNIT

Supply, Installation, testing and commissioning of table top chairman unit with microphone and built-in loudspeaker. The chairman unit shall have the following technical features or equivalent :

Electrical

Power Consumption: 9W to 20W

Frequency Response: 30 Hz to 20 KHz

THD: <0.5%

S/N : >93 dBA

Sampling Rate: 44.1 KHz

[Handwritten signatures and initials in blue and black ink, including a large signature on the left and several smaller ones across the bottom.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Acoustical

- Loudspeaker nominal output: 72 dB SPL
- Participants loudspeaker frequency response: 200 Hz to 16 kHz (acoustical)
- Microphone polar pattern: Cardioid
- Participants microphone frequency response: 125 Hz to 15 kHz
- Microphone nominal input: 85 dB SPL

Unique patent pending possible-to-speak indicator

Plug and play functionality for ensuring fast installation and reconfiguration time Immunity to mobile phone interference

Controls and Indicators

- Microphone button,
- Color-coded LED indicator above microphone button for showing the following states: microphone on request-to-speak, and possible-to-speak,
- Light-ring indicator in head of microphone
- Rotary thumbwheel on side of device for adjusting the headphones volume
- Concealed slide-switch at base of Discussion Device for configuring the Discussion Device as a 'participant Discussion Device' or 'chairperson's Discussion Device', Chairperson's configuration only – separate microphone button and 'priority button'..

Connections

- 1 x 6-pole circular female connector with cable
- locking recess – for loop-through connection of Discussion Devices
- 1 x 3.5 mm (0.14 in) stereo headphones socket on side of device
- Minimum 1 x 2 m (78.7 in) cable with a 6-pole circular male connector with cable lock

Certifications:

[Handwritten signatures and marks]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

The discussion unit conforms in general to the IEC 60914 standard.

Approvals CE, WEEE1, UL, FCC, CSA, ICES-003

Warranty: 1 Year

Accepted/approved by the engineer-in-charge.

Each	40,554.00	40,543.00	40,501.00	40,501.00
------	-----------	-----------	-----------	-----------

10.1.3 TABLE TOP DELEGATE UNIT

Supply, installation, testing and commissioning of table top delegate unit with microphone and built-in loudspeaker. The delegate unit shall have the following technical features or equivalent :

Electrical

Power Consumption : 9W to 20W

Frequency Response : 30 Hz to 20 KHz

THD : <0.5%

S/N : >93 dBA

Sampling Rate : 44.1 KHz

Unique patent pending possible-to-speak indicator

Plug and play functionality for ensuring fast installation and reconfiguration times

Immunity to mobile phone interference

Controls and Indicators

[Handwritten signatures and marks in blue ink, including a large '3' and various initials, are present below the 'Controls and Indicators' section.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

- Microphone button
- Color-coded LED indicator above microphone button for showing the following states: microphone on, request-to-speak, and possible-to-speak
- Light-ring indicator in head of microphone
- Rotary thumbwheel on side of device for adjusting the headphones volume
- Concealed slide-switch at base of Discussion Device for configuring the Discussion Device as a 'participant Discussion Device' or 'chairperson's Discussion Device', Chairperson's configuration only – separate microphone button and 'priority button'.

Connections

- 1 x 6-pole circular female connector with cable
- locking recess – for loop-through connection of Discussion Devices
- 1 x 3.5 mm (0.14 in) stereo headphones socket on side of device
- Minimum 1 x 2 m (78.7 in) cable with a 6-pole circular male connector with cable lock

Mechanical

- Mounting Tabletop (portable or fixed)
- Material (top) Plastic ABS+PC

Interconnections

LAN: Two RJ45 female sockets with auto-termination.

Mechanical

Mounting: Tabletop.

Temperature range: 5° to 45° C.

Certifications

The discussion unit conforms in general to the IEC 60914 standard

[Handwritten signatures and initials in blue and black ink, including "RDS", "GSP", "Raj", "M", "K", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "AA", "AB", "AC", "AD", "AE", "AF", "AG", "AH", "AI", "AJ", "AK", "AL", "AM", "AN", "AO", "AP", "AQ", "AR", "AS", "AT", "AU", "AV", "AW", "AX", "AY", "AZ", "BA", "BB", "BC", "BD", "BE", "BF", "BG", "BH", "BI", "BJ", "BK", "BL", "BM", "BN", "BO", "BP", "BQ", "BR", "BS", "BT", "BU", "BV", "BW", "BX", "BY", "BZ", "CA", "CB", "CC", "CD", "CE", "CF", "CG", "CH", "CI", "CJ", "CK", "CL", "CM", "CN", "CO", "CP", "CQ", "CR", "CS", "CT", "CU", "CV", "CW", "CX", "CY", "CZ", "DA", "DB", "DC", "DD", "DE", "DF", "DG", "DH", "DI", "DJ", "DK", "DL", "DM", "DN", "DO", "DP", "DQ", "DR", "DS", "DT", "DU", "DV", "DW", "DX", "DY", "DZ", "EA", "EB", "EC", "ED", "EE", "EF", "EG", "EH", "EI", "EJ", "EK", "EL", "EM", "EN", "EO", "EP", "EQ", "ER", "ES", "ET", "EU", "EV", "EW", "EX", "EY", "EZ", "FA", "FB", "FC", "FD", "FE", "FF", "FG", "FH", "FI", "FJ", "FK", "FL", "FM", "FN", "FO", "FP", "FQ", "FR", "FS", "FT", "FU", "FV", "FW", "FX", "FY", "FZ", "GA", "GB", "GC", "GD", "GE", "GF", "GG", "GH", "GI", "GJ", "GK", "GL", "GM", "GN", "GO", "GP", "GQ", "GR", "GS", "GT", "GU", "GV", "GW", "GX", "GY", "GZ", "HA", "HB", "HC", "HD", "HE", "HF", "HG", "HH", "HI", "HJ", "HK", "HL", "HM", "HN", "HO", "HP", "HQ", "HR", "HS", "HT", "HU", "HV", "HW", "HX", "HY", "HZ", "IA", "IB", "IC", "ID", "IE", "IF", "IG", "IH", "II", "IJ", "IK", "IL", "IM", "IN", "IO", "IP", "IQ", "IR", "IS", "IT", "IU", "IV", "IW", "IX", "IY", "IZ", "JA", "JB", "JC", "JD", "JE", "JF", "JG", "JH", "JI", "JJ", "JK", "JL", "JM", "JN", "JO", "JP", "JQ", "JR", "JS", "JT", "JU", "JV", "JW", "JX", "JY", "JZ", "KA", "KB", "KC", "KD", "KE", "KF", "KG", "KH", "KI", "KJ", "KK", "KL", "KM", "KN", "KO", "KP", "KQ", "KR", "KS", "KT", "KU", "KV", "KW", "KX", "KY", "KZ", "LA", "LB", "LC", "LD", "LE", "LF", "LG", "LH", "LI", "LJ", "LK", "LL", "LM", "LN", "LO", "LP", "LQ", "LR", "LS", "LT", "LU", "LV", "LW", "LX", "LY", "LZ", "MA", "MB", "MC", "MD", "ME", "MF", "MG", "MH", "MI", "MJ", "MK", "ML", "MM", "MN", "MO", "MP", "MQ", "MR", "MS", "MT", "MU", "MV", "MW", "MX", "MY", "MZ", "NA", "NB", "NC", "ND", "NE", "NF", "NG", "NH", "NI", "NJ", "NK", "NL", "NM", "NN", "NO", "NP", "NQ", "NR", "NS", "NT", "NU", "NV", "NW", "NX", "NY", "NZ", "OA", "OB", "OC", "OD", "OE", "OF", "OG", "OH", "OI", "OJ", "OK", "OL", "OM", "ON", "OO", "OP", "OQ", "OR", "OS", "OT", "OU", "OV", "OW", "OX", "OY", "OZ", "PA", "PB", "PC", "PD", "PE", "PF", "PG", "PH", "PI", "PJ", "PK", "PL", "PM", "PN", "PO", "PP", "PQ", "PR", "PS", "PT", "PU", "PV", "PW", "PX", "PY", "PZ", "QA", "QB", "QC", "QD", "QE", "QF", "QG", "QH", "QI", "QJ", "QK", "QL", "QM", "QN", "QO", "QP", "QQ", "QR", "QS", "QT", "QU", "QV", "QW", "QX", "QY", "QZ", "RA", "RB", "RC", "RD", "RE", "RF", "RG", "RH", "RI", "RJ", "RK", "RL", "RM", "RN", "RO", "RP", "RQ", "RR", "RS", "RT", "RU", "RV", "RW", "RX", "RY", "RZ", "SA", "SB", "SC", "SD", "SE", "SF", "SG", "SH", "SI", "SJ", "SK", "SL", "SM", "SN", "SO", "SP", "SQ", "SR", "SS", "ST", "SU", "SV", "SW", "SX", "SY", "SZ", "TA", "TB", "TC", "TD", "TE", "TF", "TG", "TH", "TI", "TJ", "TK", "TL", "TM", "TN", "TO", "TP", "TQ", "TR", "TS", "TT", "TU", "TV", "TW", "TX", "TY", "TZ", "UA", "UB", "UC", "UD", "UE", "UF", "UG", "UH", "UI", "UJ", "UK", "UL", "UM", "UN", "UO", "UP", "UQ", "UR", "US", "UT", "UU", "UV", "UW", "UX", "UY", "UZ", "VA", "VB", "VC", "VD", "VE", "VF", "VG", "VH", "VI", "VJ", "VK", "VL", "VM", "VN", "VO", "VP", "VQ", "VR", "VS", "VT", "VU", "VV", "VW", "VX", "VY", "VZ", "WA", "WB", "WC", "WD", "WE", "WF", "WG", "WH", "WI", "WJ", "WK", "WL", "WM", "WN", "WO", "WP", "WQ", "WR", "WS", "WT", "WU", "WV", "WW", "WX", "WY", "WZ", "XA", "XB", "XC", "XD", "XE", "XF", "XG", "XH", "XI", "XJ", "XK", "XL", "XM", "XN", "XO", "XP", "XQ", "XR", "XS", "XT", "XU", "XV", "XW", "XX", "XY", "XZ", "YA", "YB", "YC", "YD", "YE", "YF", "YG", "YH", "YI", "YJ", "YK", "YL", "YM", "YN", "YO", "YP", "YQ", "YR", "YS", "YT", "YU", "YV", "YW", "YX", "YZ", "ZA", "ZB", "ZC", "ZD", "ZE", "ZF", "ZG", "ZH", "ZI", "ZJ", "ZK", "ZL", "ZM", "ZN", "ZO", "ZP", "ZQ", "ZR", "ZS", "ZT", "ZU", "ZV", "ZW", "ZX", "ZY", "ZZ"]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	Approvals CE, KC, CCC, cUL, TUV Warranty: Minimum 1 Year Accepted/approved by the engineer-in-charge.	Each	39,940.00	39,929.00	39,888.00	39,888.00

10.1.4 EXTENSION UNIT

Supply, Installation, testing and commissioning of the Extension Unit

The Extension Unit shall have the following technical features or equivalent :

Electrical

- Supply Voltage Adaptor: 100 to 240 VAC, 50Hz
- Current Consumption Voltage Adaptor: 1.9 A (100 VAC) to 1A 240 (VAC)
- DC Voltage Control Unit: 24V, 6.0 A
- Maximum Number of Discussion Devices per Extension Unit: 40 Discussion Devices per trunk/ tap-off 85 Discussion Devices in total 24 V, Max 5.2 A (short circuited protected)

Automatic Power up: The extension unit is switched on or off automatically with the control unit

[Handwritten signatures and marks in blue and black ink, including initials and a large '3' at the bottom center.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Controls and indicators

- Front Panel: 1x power on/off

Connections

- Rear Panel:

- 1x 2 meter cable with 6 pole circular male connector for connection to the Control Unit or previous component in the daisy-chain
- 1x 6 pole circular female connector for trunk connection of the devices (maximum of 40 devices per trunk)
- 2x 6 pole circular female connectors for tap-off connection of the Discussion Devices (maximum of 40 Discussion Devices per tap-off, with a maximum of 85 Discussion Devices per Extension Unit)
- 1x 4 pole circular female 24 VDC power input connector

Environmental

Operating temperature : 5° to 45° C

Approvals CE, WEEE, UL, FCC, CSA, KCC, RCM, EAC

Warranty: Minimum 1 year

Accepted/approved by the engineer-in-charge.

Each

192,401.00

192,390.00

192,348.00

192,348.00

10.1.5 EXTENSION CABLE

Supply, Installation, testing and commissioning of extension cable. The extension cable shall have the following technical features or equivalent :

Cable terminated at both ends with a molded six-pole circular, Connector (male and female). The extension to the type number, Gives the length of the cable.

Technical Specifications

Dimensions: 6mm

Material: PVC

05m (16.5 feet), terminated with connectors

[Handwritten signatures and initials are present at the bottom of the page, including a large signature on the left and several initials and marks on the right.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	<p>Cable terminated at both ends with a molded six-pole circular Connector (male and female)</p> <p>The extension to the type number Gives the length of the cable.</p> <p>Technical Specifications</p> <p>Dimensions: 6mm</p> <p>Material: PVC</p> <p>Minimum 10m (33.0 feet), terminated with connector</p> <p>Warranty: Minimum 1 Year</p> <p>Accepted/approved by the engineer-in-charge.</p>	Each	25,154.00	25,143.00	25,102.00	25,102.00

10.2 DIGITAL CONFERENCE SYSTEM (WIRELESS)

10.2.1 Wireless Conference Access Point with web server

Supply, Installation, testing and commissioning of Wireless Conference Access Point

The Wireless Conference Access Point shall have the following technical features or equivalent:

Electrical

Supply Voltage: 24 V (24V-15W ACDC adapter), 48 V (PoC)

Power Consumption: 7W to 10W

Ethernet Port: LAN, TCP/IP

Modulation: OFDM

Transmitting Power: <20dBm

[Handwritten signatures and marks in blue and black ink, including a large '3' and various initials.]

Connectivity

Camera control integration capable

Accepted/approved by the engineer-in-charge.

331,925.00

Supply, Installation, testing and commissioning of the Wireless Conference Chairman Unit

The Wireless Conference Chairman Unit shall have the following technical features or equivalent :

Handwritten notes and symbols on lined paper, including:

- A small sketch of a person's head and shoulders.
- A large, stylized letter 'D'.
- A large, stylized letter 'P'.
- A large, stylized letter 'A'.
- A large, stylized letter 'L'.
- A large, stylized letter 'G'.
- A large, stylized letter 'B'.
- A large, stylized letter 'C'.
- A large, stylized letter 'H'.
- A large, stylized letter 'I'.
- A large, stylized letter 'J'.
- A large, stylized letter 'K'.
- A large, stylized letter 'L'.
- A large, stylized letter 'M'.
- A large, stylized letter 'N'.
- A large, stylized letter 'O'.
- A large, stylized letter 'P'.
- A large, stylized letter 'Q'.
- A large, stylized letter 'R'.
- A large, stylized letter 'S'.
- A large, stylized letter 'T'.
- A large, stylized letter 'U'.
- A large, stylized letter 'V'.
- A large, stylized letter 'W'.
- A large, stylized letter 'X'.
- A large, stylized letter 'Y'.
- A large, stylized letter 'Z'.

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	<ul style="list-style-type: none"> • Wireless chairman unit with built-in loudspeaker, microphone connector, prior and next-in-line button • GSM immune gooseneck microphone of 40 cm with bi-colour led ring indication (red / green) • Windscreen included • Lithium-ion Battery pack for wireless Conference unit • Microphone on/off or request-to-speak button with two signaling LEDs <ul style="list-style-type: none"> • Two headphone outputs • One headphone volume adjustment; Priority button; Next-in-line button • Battery and range status color LED • CE Certified • Material: PC/ABS • Audio quality: 16 bit digital • Security: Three layers with 128 bit AES encryption • Display type: OLED 128 x 64 or equivalent • Operating temperature: -5 to 55°C • Battery capacity: Minimum 6600 mAh • Battery autonomy: Minimum 28 hours on single charge • Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback. <p>Warranty: Minimum 1 Year Accepted/approved by the engineer-in-charge.</p>	Each	150,375.00	150,364.00	150,322.00	150,322.00

10.2.3 Wireless Conference Delegate Unit

Supply, Installation, testing and commissioning of the Wireless Conference Delegate Unit

The Wireless Conference Delegate Unit shall have the following technical features or equivalent :

[Handwritten signatures and initials are present below the text, including a large blue checkmark and several scribbles.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

- Wireless delegate unit with built-in speaker and microphone connector
- GSM immune gooseneck microphone of 40 cm with bi-colour led ring indication (red / green)
- Windscreen included
- Lithium-ion Battery pack for wireless Conference unit
- Microphone on/off or request-to-speak button with two signaling LEDs
- Two headphone outputs
- One headphone volume adjustment
- Next-in-line button
- Battery and range status color LED
- CE Certified

- Material: PC/ABS
- Audio quality: 16 bit digital
- Security: Three layers with 128 bit AES encryption
- Display type: OLED 128 x 64 or equivalent
- Operating temperature: -5 to 55°C
- Battery capacity: Minimum 6600 mAh
- Battery autonomy: Minimum 28 hours on single charge
- Built-in high-quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback

Warranty: Minimum 1 Year

Accepted/approved by the engineer-in-charge.

Each 140,558.00 140,547.00 140,506.00 140,506.00

10.2.4 Wireless Conference Battery Charging Tray

Charging tray for 6 battery packs 19" rack mountable

Material: PC/ABS

Supply Voltage: 100 – 230 VAC

[Handwritten signatures and initials in blue and black ink, including "AP", "R", "S", "D", "E", "H", "K", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z", "A", "B", "C", "D", "E", "F", "G", "H", "I", "J", "K", "L", "M", "N", "O", "P", "Q", "R", "S", "T", "U", "V", "W", "X", "Y", "Z"]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	Output power: 100 W Operating temperature : -100 to 60°C Loop-through mains connector CE Certified Warranty: Minimum 1 Year Accepted/approved by the engineer-in-charge.	Each	122,766.00	122,755.00	122,713.00	122,713.00

10.2.5 Two Nos Tracking Camera for Conference System Including Software

Supply, Installation, testing and commissioning of Two Nos Tracking Camera for Conference System Including Software

The Conference Camera shall have the following technical features or equivalent :

Sensor: 1/2.8" 2 MP CMOS or above

Video Output: 1080p 60 / 59.94 / 50 fps, 1080i 60 / 59.94 / 50 fps, 1080p 30 / 29.97 / 25 fps, 720p 60 / 59.94 / 50 fps

Optical Zoom: 20×

Panning Angle : -170° ~ +170°

Tilting Angle: -30° ~ +90°

Preset Positions: 128

Video Output (HD) Interface: 3G-SDI

PoE: PoE+ (IEEE802.3at)

Camera Control Interface: RS-232 / RS-422 / Ethernet

Camera Control Protocol: VISCA / PELCO D

Video S/N Ratio: > 50dB

Shutter Speed : 1/1 ~ 1/10,000 sec

Focal Length: f = 4.7 ~ 94 mm

3D NR : Yes

Horizontal Viewing Angle: 63° or above

Aperture: F1.6 ~ 3.5

Minimum Illumination: 1.0 lux (F1.6, 50 IRE, 30fps)

[Handwritten signatures and marks in blue ink at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Minimum Object Distance: 1.2m

Gain Control: Auto, manual

White Balance: Auto, indoor, outdoor, one-push, manual

Exposure Control: Auto, manual

Image Flip : Yes

Audio Input : Line In / MIC In

Audio Output: Ethernet, SDI and HDMI

Camera Software

- Software for setting up tracking camera to current speaker
- Automatic camera tracking works by creating camera presets for each microphone location in the room
- With the software, the installer can pan, tilt, and zoom the camera to different positions and can save these positions as camera presets that can be recalled automatically when microphones become active
- Two or more cameras are used to ensure the current view is shown until the second camera has moved and is ready to show its view. This ensures a smooth transition of video without showing the camera motion during the pan, tilt, or zoom maneuvers
- A camera typically takes only a second or two to move to a new position before the video switcher transitions to that camera view.

Broadcast Device

Total Video Inputs : 8 (Minimum)

Total Video Outputs : 8 (Minimum)

SDI Rates : 270Mb, 1.5G, 3G

SDI Video Inputs : 4 x 10-bit SD/HD switchable. 2 channel embedded audio

SDI Program Output : 5 x 10-bit SD/HD switch-able

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	SDI Audio Outputs : 2 Chembedded into SDI output SD Video Standards : 525i59.94 NTSC 4:3 or 16:9, 625i50 PAL 4:3 or 16:9 HD Video Standards : 720p50, 720p59.94 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p50, 1080p59.94, 1080i50, 1080i59.94 SDI Compliance : SMPTE 259M, 292M and 424M Video Sampling : 4:2:2 10-bit Color Precision : Color Space : 4:2:2 YUV Power Supply : 1 x internal 110 – 240V AC Operating Temperature : 5° C to 40° C (41° - 104°F) Storage Temperature : -10° to 60° C (14° to 140°F) Relative Humidity : 0% to 90% non-condensing Warranty : Minimum 1 Year Accepted/approved by the engineer-in-charge.	Each	1,473,133.00	1,473,122.00	1,473,080.00	1,473,080.00

10.2.5.1 Integrated Camera

Supply, Installation, testing and commissioning of integrated camera which has the following technical specification or equivalent:

Sensor : 1/2.8" 2 MP CMOS or above

Video Output : 1080p 60 / 59.94 / 50 fps, 1080i 60 / 59.94 / 50 fps, 1080p 30 / 29.97 / 25 fps, 720p 60 / 59.94 / 50 fps

Optical Zoom: 20×

Panning Angle: -170° ~ +170°

Tilting Angle: -30° ~ +90°

Preset Positions: 128

[Handwritten signatures and initials in blue ink]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	Video Output (HD) Interface : 3G-SDI PoE: PoE+ (IEEE802.3at) Camera Control Interface: RS-232 / RS-422 / Ethernet Camera Control Protocol : VISCA / PELCO D Video S/N Ratio: > 50dB Shutter Speed: 1/1 ~ 1/10,000 sec Focal Length: f = 4.7 ~ 94 mm 3D NR: Yes Horizontal Viewing Angle: 63° Aperture: F1.6 ~ 3.5 Minimum Illumination: 1.0 lux (F1.6, 50 IRE, 30fps) Minimum Object Distance: 1.2m Gain Control: Auto, manual White Balance: Auto, indoor, outdoor, one-push, manual Exposure Control: Auto, manual Focus System: Auto, manual Image Flip: Yes Audio Input : Line In / MIC In Audio Output: Ethernet, SDI and HDMI Warranty : Minimum 1 Year Accepted/approved by the engineer-in-charge.	Each	306,762.00	306,762.00	306,762.00	306,762.00

10.3 MULTIMEDIA PROJECTOR

- 10.3.1 Supply, installation, testing, commissioning multimedia projector including all necessary accessories & Warranty/Service Support of following technical specification or equivalent:

Projection Technology: RGB liquid crystal shutter projection system (3LCD)

Brightness: 5,000lm or above

Connectivity: Network: Wired LAN: RJ45 x 1

Wireless : Optional

Analog Input : D-Sub 15Pin: 2 (1 Blue, 1 Black)

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Composite : 1 Digital

Input : HDMI: 2

HDBASET (RX): N/A Output Terminal: D-Sub 15Pin: 1 (Black)

Audio Input : RCA (White/Red): 1

Stereo Mini Jack: 2 Audio Output: Stereo

Mini Jack: 1 Control

USB Type B: 1 (for USB Display, Mouse, K/B, Control, Firmware Update, Copy OSD Settings)

Contrast Ratio: 15,000:1

Screen Size (Projected Distance): Zoom : Wide: 50" - 300" [1.46 - 8.95 m]

Zoom: Tele: 50" - 300" [2.43 - 14.79 m]

Operating Temperature: Below 2,286m / 7,500ft: 5 - 40 °C <41 - 104 °F>

Above 2,286m / 7,500ft (w/ High Altitude Mode): 5 - 35 °C <41 - 95 °F>

Sound Output: 16W

Power Consumption: (220 - 240V)

Lamp On (Normal/Eco) : 405W / 323W Networked Standby (maximum)

Energy Saving: 2.41W / 0.31W

Fan Noise (Normal/Eco) : 39dB / 29dB

LCD: Size: 0.76" (D10, C2 Fine)

Native Resolution: WUXGA (1920 x 1200)

Projection Lens: Type: Optical Zoom (Manual) / Focus (Manual)

F-Number: 1.5 - 2.0

Focal Length : 23 - 38.4 mm

Zoom Ratio: 1 - 1.6

Throw Ratio: 1.38 - 2.28 (Wide to Tele) Lamp: Type: Lamp

Life (Normal / Eco)*1: 5,000 / 10,000 hours (Minimum)

[Handwritten signatures and marks in blue and black ink, including the word "for" and various initials.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Suitable for use in tropical country like BANGLADESH. Complete with required accessories and in conformity to specified codes & specification of international standards & CE / UL / CSA certified.

Warranty : Minimum 1 Year

Accepted/approved by the engineer-in-charge.

Each

257,926.00

257,815.00

257,398.00

257,398.00

- 10.3.2 Supply, installation, testing, commissioning multimedia projector including all necessary accessories & Warranty/Service Support of following technical specification or equivalent:

Projection Technology: 3LCD Technology, RGB liquid crystal shutter

LCD Panel: 0.59 inch with MLA (D9)

Image Size(Projected Distance): 33" to 320" 1.68 m - 2.02 m (60 inch screen)

Projector Lens: Optical

Lamp Type: UHE, 210 W, 6,000 h durability, 10,000 h durability (economy mode)

Native Resolution: WXGA, 1280 x 800, 16:10

Brightness: **3,300 lm or above**

Contrast Ratio: 15,000 : 1

Noise Level: 37 / 28 dB

Connectivity: USB 2.0 Type A, USB 2.0 Type B, VGA in, HDMI in, Composite in, Cinch audio in, Wireless LAN IEEE 802.11b/g/n (optional)

Environment: Temperature Operation : 5° C - 35° C, Storage -10° C - 60° C ; Humidity

Operation: 20% - 80%, Storage 10% - 90%

Sound Output: 2 Watt

Power: 282 Watt, 203 Watt (economy), 0.2 Watt (standby)

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Included Accessories: Main unit, Power cable, Quick Start Guide, Remote control incl. batteries, User manual (CD), VGA cable

Advanced Features: AV mute slide, Automatic keystone correction, Built-in speaker, Horizontal and vertical keystone correction, Long lamp life, Quick Corner

Suitable for use in tropical country like BANGLADESH. Complete with required accessories and in conformity to specified codes & specification of international standards & CE / UL / CSA certified.

Warranty : Minimum 1 Year

Accepted/approved by the engineer in charge

Each	55,463.00	55,352.00	54,935.00	54,935.00
------	-----------	-----------	-----------	-----------

10.4 MULTIMEDIA SCREEN

Supply, installation, testing, commissioning multimedia projector screen including all necessary accessories & Warranty/Service Support of following technical specification or equivalent:

10.4.1 5' x 5'

10.4.1.1 Tripod (High Contrast Gray Screen)	Each	3,681.00	3,680.00	3,676.00	3,676.00
10.4.1.2 Manual wall / ceiling screen	Each	3,558.00	3,557.00	3,554.00	3,554.00
10.4.1.3 Motorized/ Electric screen	Each	8,099.00	8,097.00	8,094.00	8,094.00

10.4.2 6' x 6'

10.4.2.1 Tripod (High Contrast Gray Screen)	Each	3,927.00	3,925.00	3,922.00	3,922.00
10.4.2.2 Manual wall / ceiling screen	Each	3,681.00	3,680.00	3,676.00	3,676.00
10.4.2.3 Motorized/ Electric screen	Each	9,326.00	9,324.00	9,321.00	9,321.00

10.4.3 7' x 7'

10.4.3.1 Tripod (High Contrast Gray Screen)	Each	7,976.00	7,975.00	7,971.00	7,971.00
10.4.3.2 Manual wall / ceiling screen	Each	6,749.00	6,748.00	6,744.00	6,744.00

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
10.4.3.3	Motorized/ Electric screen	Each	13,007.00	13,005.00	13,002.00	13,002.00
10.4.4	8' x 8'					
10.4.4.1	Tripod (High Contrast Gray Screen)	Each	11,166.00	11,165.00	11,161.00	11,161.00
10.4.4.2	Manual wall / ceiling screen	Each	9,203.00	9,202.00	9,198.00	9,198.00
10.4.4.3	Motorized/ Electric screen	Each	15,461.00	15,460.00	15,456.00	15,456.00
10.4.5	10'x7.5'					
10.4.5.1	Manual wall / ceiling screen (Manual 150" Diagonal)	Each	11,412.00	11,410.00	11,407.00	11,407.00
10.4.5.2	Motorized/ Electric screen (Motorized 150" Diagonal)	Each	20,369.00	20,368.00	20,364.00	20,364.00
10.4.6	12'x9'					
10.4.6.1	Motorized/ Electric screen (Motorized 180" Diagonal)	Each	43,069.00	43,068.00	43,064.00	43,064.00
10.4.7	14'x14'					
10.4.7.1	Motorized/ Electric screen (Motorized 238" Diagonal)	Each	76,200.00	76,198.00	76,195.00	76,195.00
10.4.8	16'x16'					
10.4.8.1	Motorized/ Electric screen (Motorized 272" Diagonal)	Each	147,369.00	147,367.00	147,364.00	147,364.00
10.5	PROFESSIONAL DISPLAY SOLUTION (INDOOR)					
10.5.1.1	Interactive Display					
10.5.1.1	Supply, installation, testing, commissioning of 65 Inch All in One Interactive Display including all necessary accessories & Warranty/Service Support of following technical specification or equivalent					

Panel

Handwritten signatures and initials are present below the text "Panel".

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Screen Size: 65 inch
 Panel Technology: IPS
 Back Light Type: M+, Direct
 Aspect Ratio : 16:9
 Native Resolution: 3,840 X 2,160 (UHD)
 Brightness: Typ: 350 cd/m2 (W/Protection Glass)
 Contrast Ratio: 1,200:1,
 Viewing Angle (HXV) : 178 X 178 (minimum)
 Response Time: 9 ms (Gto G)
 Life Time (Typ): 30,000 Hrs (Min)
 Operation Hours: 16Hrs, Orientation: Landscape

Connectivity (Input)

Video/Audio: HDMI (3) RGB / Audio In,
 External control: RS232C In, RJ45,
 USB: USB 2.0 (3, Front : 2ea, Bottom side: 1ea, Only for software update), USB 3.0 (3), Touch Out(USB2.0,B Type)

Connectivity (Output)

Video/Audio: HDMI (1), Optical Output / Audio Out

Mechanical Specification

Mount Interface: 600 X 400

Key Features

HW: Internal Memory (16GB), SoC (Hisi 811, Dual core A73+Dual core A53), DDR(3GB)
 Wi-Fi(Built-in, Slot type)
 Power Indicator, Local Key Operation(1, Power button)
 SW: Android 8.0 or updated

ENVIRONMENT CONDITIONS

Operation Temperature: 0 °C to 40 °C, Operation Humidity: 10 % to 80 %

[Handwritten signatures and marks]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

POWER

Power Supply: 100-240V~, 50Hz

Power Type: Built-In Power

Power Consumption (Maximum): 240W / 280W

SOUND

Speaker: Built in 24W (12W + 12W)

STANDARD (CERTIFICATION)

Safety: UL / cUL / CB, EMC: FCC Class "A" / CE, ErP / Energy Star: Yes / No

MEDIA PLAYER COMPATIBILITY

OPS type compatible: Yes

ACCESSORIES

Basic: Power Cord 3 M*1, USB Cable (Type A-Type B) 5 M*1, HDMI

Cable 3 M*1, Writing Pen*2pcs, User Manual, QSG, Remote Control

SPECIAL FEATURES

Embedded Writing Software: Yes

TOUCH SPECIFICATIONS

Touch type: IR, Available object

size for touch: Ø3 mm ↑

Response Time: 60ms ↓ (Android) / 100ms ↓ (Windows)

Accuracy: ±1.5mm

Interface: USB 2.0

Protection Glass Thickness: 4T (Anti-Glare)

Protection Glass Transmission: 87%

Operating System Support: Windows 7/8/10/ WindowsXP/Linux/ Mac/

Android (WindowsXP/Linux/Mac Support one point touch)

Multi touch point: Max 20 Point

Warranty : Minimum 1 Year

Accepted/approved by the engineer in charge

Each

666,359.00

666,357.00

666,354.00

666,354.00

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.5.1.2 Supply, installation, testing, commissioning of 75 Inch All in One Interactive Display including all necessary accessories & Warranty/Service Support of following technical specification or equivalent.

Panel

Screen Size: 75 inch
 Panel Technology: IPS
 Back Light Type: M+, Direct,
 Aspect Ratio: 16:9
 Native Resolution: 3,840 X 2,160 (UHD)
 Brightness: Tpy:330 cd/m2 (W/Protection Glass)
 Contrast Ratio: 1,100 : 1
 Viewing Angle (HXV): 178 X 178 or above
 Response Time: 8 ms (Gto G),
 Life Time (Typ): 30,000 Hrs (Min)
 Operation Hours: 16Hrs (Minimum)
 Orientation: Landscape

Connectivity (Input)

Video/Audio: HDMI (3), RGB / Audio In,
 External control: RS232C In, RJ45
 USB: USB 2.0 (3, Front : 2ea, Bottom side: 1ea, Only for software update), USB 3.0 (3), Touch Out(USB2.0,B Type) (2)

Connectivity (Output)

Video/Audio: HDMI (1), Optical Output / Audio Out

Mechanical Specification

VESATM Standard Mount Interface: 800 X 400

Key Features

HW: Internal Memory (16GB), SoC (Hisi 811, Dual core A73+Dual core A53), DDR(3GB), Wi-Fi(Built-in, Slot type), Power Indicator, Local Key Operation(1, Power button), SW: Android 8.0 or updated

ENVIRONMENT CONDITIONS

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Operation Temperature: 0 °C to 40 °C, Operation Humidity: 10 % to 80 %

POWER

Power Supply: 100-240V~, 50 Hz

Power Type: Built-In Power

Power Consumption(Typ./Max) : 260W / 300W

SOUND

Speaker: Built in 24W (12W + 12W)

STANDARD (CERTIFICATION)

Safety: UL / cUL / CB, EMC: FCC Class "A" / CE, ErP / Energy Star: Yes / No

MEDIA PLAYER COMPATIBILITY

OPS type compatible: Yes

ACCESSORIES

Basic: Power Cord 3 M*1, USB Cable (Type A-Type B) 5 M*1, HDMI Cable 3 M*1, Writing Pen*2pcs, User Manual, QSG, Remote Control

SPECIAL FEATURES

Embedded Writing Software: Yes

TOUCH SPECIFICATIONS

Touch type: IR

Available object size for touch: Ø3 mm ↑

Response Time: 60ms ↓ (Android) / 100ms ↓ (Windows)

Accuracy: ±1.5mm

Interface : USB 2.0

Protection Glass Thickness: 4T (Anti-Glare)

Protection Glass Transmission: 87%

Operating System Support: Windows 7/8/10/ WindowsXP/ Linux/Mac/ Android (WindowsXP/Linux/Mac Support one point touch), Multi touch point: Max 20 Point

Warranty : Minimum 1 Year

Accepted/approved by the engineer in charge

Each

927,409.00

927,407.00

927,404.00

927,404.00

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

- 10.5.1.3 Supply, installation, testing, commissioning of 86 Inch All in One Interactive Display including all necessary accessories & Warranty/Service Support of following technical specification or equivalent.

Panel

Screen Size: 86 inch
 Panel Technology: IPS
 Back Light Type: RGB, Direct
 Aspect Ratio: 16:9
 Native Resolution: 3,840 X 2,160 (UHD)
 Brightness :Typ:330 cd/m2 (W/Protection Glass)
 Contrast Ratio: 1,100 : 1
 Viewing Angle (HXV) : 178 X 178 (minimum)
 Response Time : 8 ms (Gto G)
 Life Time (Typ): 30,000 Hrs (Min)
 Operation Hours: 16Hrs, Orientation: Landscape

Connectivity (Input)

Video/Audio: HDMI (3), RGB / Audio In
 External control: RS232C In, RJ45
 USB: USB 2.0 (3, Front : 2ea, Bottom side: 1ea, Only for software update), USB 3.0 (3), Touch Out(USB2.0,B Type) (2)

Connectivity (Output)

Video/Audio: HDMI (1), Optical Output / Audio Out

Mechanical Specification

VESATM Standard Mount Interface: 800 X 600

Key Features

HW: Internal Memory (16GB), SoC (Hisi 811, Dual core A73+Dual core A53), DDR(3GB), Wi-Fi(Built-in, Slot type), Power Indicator, Local Key Operation(1, Power button), SW: Android 8.0 or updated

ENVIRONMENT CONDITIONS

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Operation Temperature: 0 °C to 40 °C, Operation Humidity: 10 % to 80 %

POWER

Power Supply: 100-240V~, 50 Hz

Power Type: Built-In Power

Power Consumption(Typ./Max): 400W / 450W

SOUND

Speaker: Built in 24W (12W + 12W)

STANDARD (CERTIFICATION)

Safety : UL / cUL / CB, EMC: FCC Class "A" / CE, ErP / Energy Star:

MEDIA PLAYER COMPATIBILITY

OPS type compatible: Yes

ACCESSORIES

Basic : Power Cord 3 M*1, USB Cable (Type A-Type B) 5 M*1, HDMI

Cable 3 M*1; Writing Pen*2pcs, User Manual, QSG, Remote Control

SPECIAL FEATURES

Embedded Writing Software: Yes

TOUCH SPECIFICATIONS

[Handwritten signatures and marks are present below the TOUCH SPECIFICATIONS section.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	Touch type: IR Available object size for touch : Ø3 mm ↑ Response Time : 60ms ↓ (Android) / 100ms ↓ (Windows) Accuracy: ±1.5mm Interface: USB 2.0 Protection Glass Thickness: 4T (Anti-Glare) Protection Glass Transmission: 87% Operating System Support: Windows 7/8/10/ WindowsXP/Linux/Mac/ Android (WindowsXP/ Linux/Mac Support one point touch) Multi touch point: Maximum 20 Point Warranty : Minimum 1 Year Accepted/approved by the engineer in charge	Each	1,203,781.00	1,203,780.00	1,203,776.00	1,203,776.00

10.5.2 Indoor LED Video Wall (Category A)

10.5.2.1 Supply, installation, testing and commissioning of Indoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 2.97mm

Brightness: Minimum 1000 nits Brightness

Pixel Density: Minimum 112,896 (pixels/m²)

Visual Viewing Angle (Horizontal/Vertical) : 160°/160° or above

Power Supply (V) : 100 to 240V AC 50Hz

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 2880

Operating Temperature: -10°C to +45°C

[Handwritten signatures and marks in blue ink at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

IP Rating (Front / Rear) : IP30 / IP30 minimum

Certification: CE,FCC,ETL

Warranty : Minimum 1 year

Brand: product of South Korea, Japan, EU Countries or equivalent accepted/approved by the engineer-in-charge.

Per Sqft 63,254.00 63,252.00 63,249.00 63,249.00

10.5.2.2 Supply, installation, testing and commissioning of Indoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 1.25mm

Brightness: Minimum 600 nits to 1200 nits Brightness

Pixel Density: Minimum 640,000 (pixels/m²)

Visual Viewing Angle (Horizontal/Vertical) : 1700/1700 or above

Power Supply (V): 100 to 240 V AC 50 Hz

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840

IP Rating (Front / Rear): IP20 / IP20 Minimum

Certification: ISO, RoHS, Safety 60950-1, EMC Class B

Warranty : Minimum 1 year

Brand: product of South Korea, Japan, EU Countries or equivalent accepted/approved by the engineer-in-charge.

Per Sqft 325,411.00 325,410.00 325,407.00 325,407.00

10.5.3 Indoor LED Video Wall (Category B)

10.5.3.1 Supply, installation, testing and commissioning of Indoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

[Handwritten signatures and marks at the bottom of the page]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Pixel Pitch: Maximum 3.12mm

Brightness: Minimum 800 nits Brightness

Pixel Density: Minimum 100,000 pixels/m²

Visual Viewing Angle (Horizontal/Vertical) : 140°/140° or above

Power Supply (V) : 110-220 V AC, 50 Hz

Operating Temperature: -10°C to + 40°C

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 2880

IP Rating (Front / Rear) : front IP30 minimum/rear IP21 minimum

CE certified

Warranty : Minimum 1 year

Installation with Controller, Processor & Mounting accessories &

Warranty/Service Support

Per Sqft

19,295.00

19,294.00

19,290.00

19,290.00

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.5.3.2 Supply, installation, testing and commissioning of Indoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: 1.25mm

Brightness : 600 nits Brightness

Visual Viewing Angle (Horizontal/Vertical) : 1600/1600 or above

Pixel Density: 640,000 pixels/m2 or above

Power Supply (V): 110-220 V AC, 50 Hz

Operating Temperature : -100C to + 400C

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840 Hz

IP Rating (Front / Rear) : Front IP20 minimum/ Rear IP20 minimum

CE certified

Warranty : Minimum 1 year

Installation with Controller, Processor & Mounting accessories & Warranty/Service Support

Per Sqft

78,996.00

78,995.00

78,991.00

78,991.00

[Handwritten signatures and marks are present below the table, including a large signature on the left, a signature in the middle, and several initials and marks on the right.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.5.3.3 Supply, installation, testing and commissioning of Indoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: 1.87mm

Brightness: 600 nits Brightness

Visual Viewing Angle (Horizontal/Vertical) : 1600/1600 or above

Pixel Density: 284,444 pixels/m2 or above

Power Supply (V): 110-220 V AC, 50 Hz

Operating Temperature: -100C to + 400C

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840 Hz

IP Rating (Front / Rear) : Front IP40 minimum/ Rear IP21 minimum

CE certified

Warranty : Minimum 1 year

Installation with Controller, Processor & Mounting accessories & Warranty/Service Support

Per Sqft

56,637.00

56,635.00

56,632.00

56,632.00

10.6 PROFESSIONAL DISPLAY SOLUTION (OUTDOOR)

10.6.1 Category A

10.6.1.1 Outdoor LED Video Wall Display

Handwritten signatures and marks are present below the section header, including a large '3' at the bottom left and various scribbles and initials across the page.

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Supply, installation, testing and commissioning of Outdoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 3.91mm

Brightness: Minimum 5000 nit

Pixel Density: Minimum 65,536 pixels/m²

Visual Viewing Angle (Horizontal x Vertical) : 160° × 155° or higher

Contrast Ratio : 6,000 or higher

Power Supply (V) : 100 to 240 V AC 50 Hz

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840

IP Rating (Front) : IP65X minimum

IP Rating (Rear) : IP65X minimum

Operating Temperature : -20°C to +45°C

900 Corner option, IP rated weatherproof Design

Two cabinet options

Certificates: ISO, FCC, CE, RoHS etc

Warranty : Minimum 1 year

product of South Korea, Japan, EU Countries or equivalent accepted/approved by the engineer-in-charge.

Per Sqft

96,015.00

96,014.00

96,011.00

96,011.00

[Handwritten signatures and initials are present below the table, including 'Per Sqft', '96,015.00', '96,014.00', '96,011.00', and '96,011.00'. There are also various scribbles and marks.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.6.1.2 Outdoor LED Video Wall Display

Supply, installation, testing and commissioning of Outdoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 4.63mm

Brightness: Minimum 5000 nit

Pixel Density: Minimum 46,656 pixels/m²

Visual Viewing Angle (H x V) : 1600 × 1350 or higher

Contrast Ratio: 11,000 or higher

Power Supply (V) : 100 to 24 V AC 50Hz

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840

IP Rating (Front): IP65X minimum

IP Rating (Rear) : IP65X minimum

Operating Temperature : -200C to +450C

Certificates: FCC, CE, ETL etc

900 Corner option, IP rated weatherproof Design

Two cabinet options

Warranty : Minimum 1 year

Brand: product of South Korea, Japan, EU Countries or equivalent accepted/approved by the engineer-in-charge.

Per Sqft

79,618.00

79,617.00

79,613.00

79,613.00

10.6.1.3 Outdoor LED Video Wall Display

[Handwritten signatures and marks are present below the section header, including a large blue 'X' and various scribbles.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Supply, installation, testing and commissioning of Outdoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 6.6mm

Brightness: Minimum 5000 nit

Pixel Density: Minimum 22,500 pixels/m²

Visual Viewing Angle (H x V) : 160° × 120° or higher

Contrast Ratio : 11,000 or higher

Power Supply (V) : 100 to 240 V AC 50Hz

Frame Rate (Hz): 50/60

Refresh Rate (Hz): Minimum 3840

IP Rating (Front) : IP65X minimum

IP Rating (Rear) : IP65X minimum

Operating Temperature : -20°C to +50°C

Certificates: FCC, CE, RoHS etc

90° Corner option, IP rated weatherproof Design

Two cabinet options

Warranty : Minimum 1 year

Brand: product of South Korea, Japan, EU Countries or equivalent accepted/approved by the engineer-in-charge.

Per Sqft

77,288.00

77,287.00

77,283.00

77,283.00

[Handwritten signatures and initials are present below the table, including a large signature on the left and several initials and smaller signatures on the right.]

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

10.6 **PROFESSIONAL DISPLAY SOLUTION (OUTDOOR)**

10.6.2 **Category B**

10.6.2.1 Supply, installation, testing and commissioning of Outdoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

Pixel Pitch: Maximum 8mm

Brightness: Minimum 5500 nits

Viewing Angle(Horizontal/Vertical): H1400/V1000 or above

Pixel Density: Minimum 15,625 dot/m2

Front iP65/Rear iP54

Operating Temperature : -200 C to + 400 C

Frame Rate : 50/60 Hz

Refresh rate : 1920 Hz

CE certified

Warranty : Minimum 1 year

accepted/approved by the engineer-in-charge.

Installation with Controller, Processor & Mounting accessories &

Warranty/Service Support

Per Sqft

21,964.00

21,963.00

21,959.00

21,959.00

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
10.6.2.2	Supply, installation, testing and commissioning of Outdoor LED Video Wall Display including Controller, Processor & Mounting accessories of following specifications or equivalent: Pixel Pitch :Maximum 6.67mm Brightness:Minimum 5500 nits viewing Angle:Minimum H1400/V1000 Pixel Density:Minimum 15,625 dot/m ² Front IP65/Rear IP54 Operating Temperature : -200 C to + 400 C Frame Rate : 50/60 Hz Refresh Rate : 1920 Hz CE certified Warranty : Minimum 1 year Accepted/approved by the engineer-in-charge. Installation with Controller, Processor & Mounting accessories & Warranty/Service Support					

Per Sqft

26,259.00

26,258.00

26,254.00

26,254.00

10.7 Floor Standing Display

Supply, installation, testing and commissioning of Floor Standing Display including Controller, Processor & Mounting accessories of following specifications or equivalent:

10.7.1 Floor Standing Display 43"

Screen : Minimum 43" Commercial LCD Display
Resolution: 1920 x 1080 or higher
Display Area: Minimum 943.2 x 531.4 mm
Viewing Angle : Minimum H178°, V178°
Brightness : 350cd/m² or higher
Contrast Ratio : Minimum 4000:1
Response Time : Maximum 6ms
Lifetime : ≥60000 hours
CPU : Quad-core ARM Cortex or higher

S

a

Sup

S

S

S

S

x

S

S

S

S

S

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	RAM : Minimum 2GB ROM : Minimum 8 GB Built in OS : Android 5.1 or higher Control System : Software Based Central Control Control Software Features : Server based Central Content Management via Internet, Multiple-Screen Broadcasting, Multiple Screen Split option, Minimum 3000 units of Kiosk should be controlled by single software, Scheduled Program Upload, Real-time Update Broadcast Program Type : Picture, Video, Text, Date, Time, Weather, Website, Document. (Must be ensured) USB Input : USB2.0 x minimum 2 I/O Interface: SD card slot x minimum 1, Power switch x minimum 1 Wi-Fi: Built in 802.11b/g/n RJ45 : Yes Speaker : Built in minimum 10W x2 ON/OFF Function : Remote control Video Color System: PAL/NTSC/SECAM Video Format : WMV, AVI, FLV, MPEG, MP4 etc. Audio Format : MP3, WMA, WAV, AAC, M4A etc. Image Format : BMP, JPEG, PNG, GIF etc. Image Resolution : 480P/720P/1080P or better Menu Language : English Orientation : Portrait Frame : Aluminium Profile Glass : Tempered glass Certificates : ISO9001, CCC, CE, FCC, ROHS Warranty: Minimum 1 year	Each	135,098.00	135,097.00	135,093.00	135,093.00

10.7.2 Floor Standing Display 55"

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
----------	----------------------	------	---	--	--	--------------------------------------

Screen: Minimum 55" Commercial LCD Display

Resolution: 1920 x 1080 or higher

Display Area: Minimum 1210 x 682 mm

Viewing Angle : Minimum H178, V178

Brightness : 350cd/m² or higher

Contrast Ratio : Minimum 4000:1

Response Time : Maximum 6ms

Lifetime : ≥ 60000 hours

CPU : Quad-core ARM Cortex or higher

RAM : Minimum 2GB

ROM : Minimum 8 GB

Built in OS : Android 5.1 or higher

Control System : Software Based Central Control

Control Software Features : Server based Central Content Management via

Internet, Multiple-Screen Broadcasting, Multiple Screen Split option,

Minimum 3000 units of Kiosk should be controlled by single software,

Scheduled Program Upload, Real-time Update

Broadcast Program Type : Picture, Video, Text, Date, Time, Weather,

Website, Document. (Must be ensured)

USB Input : USB2.0 x minimum 2

I/O Interface: SD card slot x minimum 1, Power switchx minimum 1

Wi-Fi: Built in 802.11b/g/n ; RJ45 : Yes

A collection of handwritten signatures and marks in black and blue ink. The marks include several stylized signatures, some with initials, and a few simple symbols like a checkmark and a circle. The handwriting is cursive and somewhat潦草.

Screen: Minimum 65" Commercial LCD Display
Resolution: 1920 x 1080 or higher
Display Area : Minimum 1428.48 x 803.52 mm
Viewing Angle : Minimum H178, V178
Brightness : 350cd/m² or higher
Contrast Ratio : Minimum 4000:1
Response Time : Maximum 6ms
Lifetime : ≥60000 hours
CPU : Quad-core ARM Cortex or higher
RAM : Minimum 2GB
ROM : Minimum 8 GB
Built in OS : Android 5.1 or higher
Control System : Software Based Central Control

Item No.	Description of Items	Unit	Unit Rate in Dhaka & Mymensingh Zone (Tk)	Unit Rate in Chattogram & Sylhet Zone (Tk)	Unit Rate in Khulna, Barishal & Gopalganj (Tk)	Unit Rate in Rajshahi & Rangpur (Tk)
	<p>Control Software Features : Server based Central Content Management via Internet, Multiple-Screen Broadcasting, Multiple Screen Split option, Minimum 3000 units of Kiosk should be controlled by single software, Scheduled Program Upload, Real-time Update</p> <p>Broadcast Program Type : Picture, Video, Text, Date, Time, Weather, Website, Document. (Must be ensured)</p> <p>USB Input : USB2.0 x minimum 2</p> <p>I/O Interface: SD card slot x minimum 1, Power switch x minimum 1</p> <p>Wi-Fi: Built in 802.11b/g/n</p> <p>RJ45 : Yes</p> <p>Speaker : Built in minimum 10W x2</p> <p>ON/OFF Function : Remote control</p> <p>Video Color System: PAL/NTSC/SECAM</p> <p>Video Format : WMV, AVI, FLV, MPEG, MP4 etc.</p> <p>Audio Format : MP3, WMA, WAV, AAC, M4A etc.</p> <p>Image Format : BMP, JPEG, PNG, GIF etc.</p> <p>Image Resolution : 480P/720P/1080P or better</p> <p>Menu Language : English</p> <p>Orientation : Portrait</p> <p>Frame : Aluminium Profile</p> <p>Glass : Tempered glass</p> <p>Certificates : ISO9001, CCC, CE, FCC, ROHS</p> <p>Warranty: Minimum 1 year</p>	Each	208,721.00	208,720.00	208,716.00	208,716.00

Handwritten signatures and initials are present below the table, including a large signature on the left, several smaller signatures in the middle, and a signature on the right with a blue checkmark.